

Tapes RoHS and REACH Compliant

Applications: Aerospace, Automotive, Construction, Display or Mirror or Sign Mounting



Double Sided Foam Tapes

Bertech Part Number	Description	Weight (lbs.)
1/16 inches Thick Double Sided White PE Foam tapes		
DSFT-1/4	1/16 inches thick x 1/4 inches wide x 36 yards long, Double Sided Foam Tape	0.30
DSFT-3/8	1/16 inches thick x 3/8 inches wide x 36 yards long, Double Sided Foam Tape	0.35
DSFT-1/2	1/16 inches thick x 1/2 inches wide x 36 yards long, Double Sided Foam Tape	0.40
DSFT-3/4	1/16 inches thick x 3/4 inches wide x 36 yards long, Double Sided Foam Tape	0.45
DSFT-1	1/16 inches thick x 1 inches wide x 36 yards long, Double Sided Foam Tape	0.50
DSFT-1 1/2	1/16 inches thick x 1 1/2 inches wide x 36 yards long, Double Sided Foam Tape	0.60
DSFT-2	1/16 inches thick x 2 inches wide x 36 yards long, Double Sided Foam Tape	0.70
DSFT-4	1/16 inches thick x 4 inches wide x 36 yards long, Double Sided Foam Tape	4.00

Double Sided Foam Tapes

Double Sided Foam Tapes are made of a closed-cell, cross linked polyethylene foam, coated on both sides with a high performance Acrylic adhesive and glassine paper liner. These double sided foam tapes are designed as an alternate to screws and bolts for mounting applications. They are ideal for mounting or adhering two rigid objects together. They are easy to apply by having peel away liners. Bertech's double sided foam tapes conform to most solid smooth surfaces. They are available in widths of up to 40 inches width and 1/16 inch or 1/8 inch thick material.

Custom sizes are available upon request.

Part Number	DSFT series	Adhesion	70 oz./in.
Material	PE Foam	Foam Density	3 to 6 per cubic foot (PCF)
Thickness	1/16, 1/8 inches	Elongation	300%
Liner	Glassine	Cohesion	>240 hr.
Color	White	Standards	PSTC-31 and 33, ASTM-D-1000
Adhesive	Solvent Acrylic	UNSPSC Code	31201527