

Tapes RoHS and REACH Compliant

Applications: General Purpose ESD Tape Applications, Sealing and shipping of ESD packages and boxes, Securing IC DIP tubes, ESD Symbol for ESD caution



**Bertech Part
Number**

Description

Weight (lbs.)

ESD General Purpose Tapes

ESDCT3C-1/2	1/2 inches wide x 72 yards long, ESD General Purpose Tape, Clear	0.75
ESDCT3C-3/4	3/4 inches wide x 72 yards long, ESD General Purpose Tape, Clear	1.10
ESDCT3C-1	1 inches wide x 72 yards long, ESD General Purpose Tape, Clear	1.50
ESDCT3C-2	2 inches wide x 72 yards long, ESD General Purpose Tape, Clear	3.00

ESD General Purpose Tapes with ESD Symbol

ESDCT3P-1/2	1/2 inches wide x 72 yards long, ESD General Purpose Tape with ESD Symbol	0.75
ESDCT3P-3/4	3/4 inches wide x 72 yards long, ESD General Purpose Tape with ESD Symbol	1.10
ESDCT3P-1	1 inches wide x 72 yards long, ESD General Purpose Tape with ESD Symbol	1.50
ESDCT3P-2	2 inches wide x 72 yards long, ESD General Purpose Tape with ESD Symbol	3.00

ESD General Purpose Tapes

ESD General Purpose Tapes are made of a 2 mil cellulose material coated with a solvent based rubber adhesive. The rubber adhesive provides an excellent tack and holding power. They are ideal for general packaging in environments where a static charge is an issue. These ESD general purpose Tapes are biodegradable and can be cut by hand. These Tapes are available on a 3" core and are 108 feet long. They are available as clear tape as well as clear tape with an ESD symbol printed on it.

Part Number ESDCT3 series

Material Cellulose

Total Thickness 2 Mil ±10%

Adhesion 34 oz./inch

Holding Strength 1/32" per two hours

Temperature Range 32° F to 150° F

Adhesive Solvent Based Rubber
Color Clear & with ESD symbol
Standards ESD S20.20, CID-AA-113B, Type 1, Class A

Tensile Strength 24 lbs./inch
Elongation 22%
UNSPSC Code 31201518

