## Masking Discs RoHS and REACH Compliant Applications: Anodizing, E-Coating, General Purpose Masking, Powder Coating, Photo Splicing



Bertech Part Number	Description	Weight (lbs)		
Green Masking Discs				
GPD-1/8	1/8 inches Green Masking Discs, 2000 Discs/Roll	0.75		
GPD-1/4	1/4 inches Green Masking Discs, 2000 Discs/Roll	0.75		
GPD-3/8	3/8 inches Green Masking Discs, 2000 Discs/Roll	0.75		
GPD-1/2	1/2 inches Green Masking Discs, 2000 Discs/Roll	0.75		
GPD-3/4	3/4 inches Green Masking Discs, 1000 Discs/Roll	1.10		
GPD-1	1 inches Green Masking Discs, 500 Discs/Roll	1.50		
GPD-2	2 inches Green Masking Discs, 100 Discs/Roll	3.00		

## **Green Masking Discs**

Green Masking Discs are made of 2 mil thick polyester film and 1.5 mil thick silicone adhesive. They can be removed cleanly without leaving any residue. These Green Masking Discs are designed for high performance, flexibility and exposure to higher temperature. They are available in diameters of up to 9 inches.

## Custom sizes are available upon request.

Material         Polyester         Tensile Strength         50 lbs./in.           Total Thickness         3.5 Mil ±10%         Elongation         >70%           Adhesive         Silicone         Operating Temperature         400° F           Standards         D3330, D3652, D3759         UNSPSC Code         60121135	Part Number	GPD series	Adhesion to Steel	46 oz./in.
Adhesive Silicone  Color Green Operating Temperature 400° F	Material	Polyester	Tensile Strength	50 lbs./in.
Color Green Operating Temperature 400° F	Total Thickness	3.5 Mil ±10%	Elongation	>70%
	Adhesive	Silicone		
Standards         D3330, D3652, D3759         UNSPSC Code         60121135	Color	Green	Operating Temperature	400° F
	Standards	D3330, D3652, D3759	UNSPSC Code	60121135