

Tapes RoHS and REACH Compliant

Applications: Anodizing, E-Coating, General Purpose Masking, Powder Coating, Photo Splicing



Bertech Part Number

Description

Weight (lbs.)

Green Masking Tapes

GPT-1/8	1/8 inches wide x 72 yards long, Green Masking Tape	0.25
GPT-1/4	1/4 inches wide x 72 yards long, Green Masking Tape	0.30
GPT-3/8	3/8 inches wide x 72 yards long, Green Masking Tape	0.35
GPT-1/2	1/2 inches wide x 72 yards long, Green Masking Tape	0.40
GPT-3/4	3/4 inches wide x 72 yards long, Green Masking Tape	0.45
GPT-1	1 inches wide x 72 yards long, Green Masking Tape	0.50
GPT-1 1/2	1 1/2 inches wide x 72 yards long, Green Masking Tape	0.60
GPT-2	2 inches wide x 72 yards long, Green Masking Tape	0.70
GPT-3	3 inches wide x 72 yards long, Green Masking Tape	1.50
GPT-4	4 inches wide x 72 yards long, Green Masking Tape	2.00

Green Masking Tapes

Green Masking Tapes are made of 2 mil thick polyester film and 1.5 mil thick silicone adhesive. They can be removed cleanly without leaving any residue. These Green Masking Tapes are designed for high performance, flexibility and exposure to higher temperature. They are packaged as 72 yard-long rolls on a 3" core. They are available in widths of up to 28 inches.

Custom sizes are available upon request.

Part Number	GPT series	Adhesion to Steel	30 oz./in.
Material	Polyester	Tensile Strength	50 lbs./in.
Total Thickness	3.5 Mil ±10%	Elongation	100%
Adhesive	Silicone	Dielectric Strength	7,000 Volts
Color	Green	Operating Temperature	400° F
Standards	D3330, D3652, D3759	UNSPSC Code	60121135