

**Tapes RoHS and REACH Compliant**

**Applications: Aisle marking and safety warning in an industrial and warehouse environments.  
Safety warning and traffic control in public places.**



**Safety Warning Tapes**

| <b>Bertech Part Number</b>                | <b>Description</b>  | <b>Weight (lbs.)</b> |
|---|---|----------------------|
| <b>2 inches Wide Safety Warning Tapes</b> |   |                      |
| BERST-2BW                                 | 2 inches Wide x 18 yards long, Black and White Safety Warning Tape  | 0.35                 |
| BERST-2BY                                 | 2 inches Wide x 18 yards long, Black and Yellow Safety Warning Tape | 0.25                 |
| BERST-2GW                                 | 2 inches Wide x 18 yards long, Green and White Safety Warning Tape  | 0.6                  |
| BERST-2RW                                 | 2 inches Wide x 18 yards long, Red and White Safety Warning Tape    | 0.45                 |
| <br>                                      |   |                      |
| BERST-3BW                                 | 3 inches Wide x 18 yards long, Black and White Safety Warning Tape  | 0.35                 |
| BERST-3BY                                 | 3 inches Wide x 18 yards long, Black and Yellow Safety Warning Tape | 0.25                 |
| BERST-3GW                                 | 3 inches Wide x 18 yards long, Green and White Safety Warning Tape  | 0.6                  |
| BERST-3RW                                 | 3 inches Wide x 18 yards long, Red and White Safety Warning Tape    | 0.45                 |

**Safety Warning Tapes**

Safety Warning Tapes are made of 7 mil thick soft PVC with rubber-based pressure sensitive adhesive. They are available in all OSHA colors. They are designed for safety marking in a manufacturing or warehouse environment. These safety warning tapes are packaged in 18 yard-long rolls on a 3 inch core. They are available in widths of up to 48 inches.

**Custom color stripes and sizes are available upon request.**

|                        |   |                           |            |
|------------------------|---|---------------------------|------------|
| <b>Part Number</b>     | BERST series                                      | <b>Adhesion to Steel</b>  | 22 oz./in. |
| <b>Material</b>        | SPVC  | <b>Tensile Strength</b>   | 18 lb./in. |
| <b>Total Thickness</b> | 7 Mil ±10%  | <b>Elongation</b>         | 150%       |
| <b>Color</b>           | Black/White, Black/Yellow, Green/White, Red/White | <b>Temperature Rating</b> | 140° F     |
| <b>Adhesive</b>        | Solvent Rubber                                    | <b>UNSPSC Code</b>        | 41122703   |